



Ghisellini Srl

GIUNTO INTEGRATO ANV 250



Il giunto "ANV" è di costruzione rigida, semplice, compatto, razionale, di lunga durata ed economico.
Il giunto "ANV" è composto da una flangia esterna in acciaio, una parte interna in nylon stampato e da un mozzo in acciaio temprato: queste caratteristiche lo rendono molto resistente all'olio.
Il giunto "ANV" è studiato per trasmettere il moto dal motore diesel a pompe idrostatiche: ad ingranaggi, a palette o a pistoni assiali, a media ed alta pressione, per circuiti aperti e chiusi.

The "ANV" flexible coupling have a rigid construction, they are simple, compact ad rational, and by garanting a long lifetime they result to be economical.

The "ANV" flexible coupling have a molded outer flange in steel, inner part in nylon and tempered steel inner hub: there characteristics make them very resistant to any oil.

Ghisellini srl

Via del Lavoro, 9 44041 -Casumaro (Fe)
Reg. Imp. / Cod. Fiscale / P. IVA: 02066970381
E.Mail: info@officinaghisellini.it
Tel 051/6849978 - Fax 051/6846852



The "ANV" flexible couplings are designed to transmit the power from a diesel engine to hydraulic pumps of any type: gear pumps, blade pumps and axial pistons pumps, medium and high pressure, for open and close circuit.

Tipo Size	Momento torcente Nominal torque Nm	Max momento torcente Max torque Nm	Nr. Giri max Max rotation speed Rpm	Momento d'inerzia J Kpm2
250	1200	2400	4000	0.0035

Ghisellini srl

Via del Lavoro, 9 44041 -Casumaro (Fe)
 Reg. Imp. / Cod. Fiscale / P. IVA: 02066970381
 E.Mail: info@officinaghisellini.it
 Tel 051/6849978 - Fax 051/6846852

